

**PHONE & EMAIL ADVICE – SECURE ONLINE ORDERS OR CALL OUR OFFICE**  
**DISCREET OVERNIGHT EXPRESS POSTAGE AUSTRALIA WIDE**



## **Towing Trailer Suzy Coil 4 Camera Cable**

**Model Number – DIN-T70**

### **Short Description**

This is a *Trailer, Truck & Caravan 4 camera Towing kit with Suzy Coil* designed for our AHD cameras and monitors. This flexible Suzy coil interface cable extend 0.5-4m. It's designed for an easy connect between the trailer and towing vehicle monitor. When selecting AHD (Analogue High Definition) monitors and cameras, ensure the DIN cables are AHD compliant. AHD has a thicker and shielded inner copper core specially designed for our camera systems and trailer coupling.

### **Description**

Ideal for *cars, buses, trucks, forklifts, agricultural vehicles, heavy machinery, tractors, trailers, caravans, semi-trailers, horse floats* and so much more.

1080P AHD is double the resolution of standard 600TVL reversing cameras. High resolution AHD monitors and cameras demand higher quality connection cables. These cables and couplings are waterproof. The 4 inner connecting pins power the cameras whilst video and audio it transmitted through the same lead.

The DIN-T70 supports up to 4 cameras simultaneously. This is the cameras to monitor Suzy Cable coupling. If 1-4 cameras are connected to the trailer, each camera will require an optional plug in DIN cable available from Hidden Camera Surveillance. DIN cable/s are available in various lengths from 5-20m. If choosing this particular 4 camera coupling, 2 DIN cables per camera are required, assuming that each camera is fixed to the trailer or float etc.



This trailer camera Suzy coli connection kit is primarily designed to easy connect and disconnect the trailer and cameras from the towing vehicle and quad view monitor.

If two cameras are fixed to the trailer, other than the pictured coupling above, 2 x DIN cables (you choose cable length) are required for each camera. One Din cable to the camera trailer and the other DIN cable to the towing vehicle monitor.

### Wireless Camera Systems

Our Wireless cameras and monitors don't require DIN cables or a coupling interface which is another option to consider. However, each wireless camera must be connected to vehicle 12V power. Cabled *CCTV mobile cameras* of course are far less vulnerable to wireless transmission interference.

### Specifications

Coiled Cable length 50cm

4 x AHD 4 PIN Cable connectors

Heavy Duty truck to trailer easy release waterproof connections



Hidden Camera Surveillance